UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/663,807	09/17/2003	Eiji Hayashi	Q77558	4057	
65565 SUGHRUE-265	7590 05/07/2009 1550	9	EXAMINER		
2100 PENNSY	LVANIA AVE. NW		BOES, TERENCE		
WASHINGTO	N, DC 20037-3213		ART UNIT	PAPER NUMBER	
			3656		
			MAIL DATE	DELIVERY MODE	
			05/07/2009	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Communication		Application No	D. Applicant(s)					
		10/663,807		HAYASHI, EIJI				
Office Action Sumn	Examiner		Art Unit					
		TERENCE BOE	s	3656				
The MAILING DATE of this Period for Reply	communication app	ears on the cove	r sheet with the c	orrespondence ad	ddress			
A SHORTENED STATUTORY PE WHICHEVER IS LONGER, FROM - Extensions of time may be available under the after SIX (6) MONTHS from the mailing date - If NO period for reply is specified above, the r - Failure to reply within the set or extended per Any reply received by the Office later than thr earned patent term adjustment. See 37 CFR	A THE MAILING DA e provisions of 37 CFR 1.13 of this communication. maximum statutory period w iod for reply will, by statute, ee months after the mailing	ATE OF THIS CO 36(a). In no event, how vill apply and will expire , cause the application	OMMUNICATION vever, may a reply be time. SIX (6) MONTHS from to become ABANDONEI	L. ely filed the mailing date of this of (35 U.S.C. § 133).	•			
Status								
1) Responsive to communicati	on(s) filed on <i>13 At</i>	pril 2009						
2a) ☐ This action is FINAL .	• •	action is non-fir	al.					
'—	/—			secution as to the	e merits is			
·— · · ·	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.							
Disposition of Claims	·		·					
4)⊠ Claim(s) <u>1-15,23,28,29 and</u>	33 is/are nending i	n the application	1					
5) Claim(s) is/are allow	4a) Of the above claim(s) is/are withdrawn from consideration.							
6)⊠ Claim(s) <u>1-15,23,28,29 and</u>								
· · ·	-							
• • • • • • • • • • • • • • • • • • • •		r alastian raquire	vm ont					
8) Claim(s) are subject	to restriction and/or	r election require	illent.					
Application Papers								
9)☐ The specification is objected								
10)⊠ The drawing(s) filed on <u>09/1</u>	<u>7/2003</u> is/are: a) <u> </u>	accepted or b)	☑ objected to by	the Examiner.				
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).								
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).								
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.								
Priority under 35 U.S.C. § 119								
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 								
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing 3) Information Disclosure Statement(s) (PT Paper No(s)/Mail Date		4)	Interview Summary Paper No(s)/Mail Da Notice of Informal Pa Other:	te				

Art Unit: 3656

DETAILED ACTION

Request for Continued Examination

1. The request filed on 01/12/2009 for a Continued Examination (RCE) is accepted and a continued prosecution application has been established. An action on the RCE follows.

Drawings

2. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, the tube guide insertion hole is a through hole which penetrates the nut, and wherein an entire depth of the tube guide insertion hole has an equal cross-section must be shown or the feature(s) canceled from the claim(s). See further discussion in 35 USC 112 section below. No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. Each drawing sheet submitted after the filing date of an

application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Claim Rejections - 35 USC § 112

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

3. Claims 1-15, 28, 29, 23 and 33 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claims 1 and 11 recite "the tube guide insertion hole is a through hole which penetrates the nut, and wherein an entire depth of the tube guide insertion hole has an equal cross-section", rendering the claims indefinite. The recitation does not appear to be supported by the original disclosure. While applicants' figures 1 and 3 appear to support the recitation, it is noted that these views are two dimensional in nature and do not provide a complete picture of the recited "through hole". A view taken from an axial perspective reveals that hole 9 is not a "through" hole in that the hole must terminate at a surface on the nut. Further, the hole cannot have an "equal cross-section" as the threaded shaft passing through the nut does not allow for this. See for example applicant's figure 4D, showing an axial cross-section, which shows the **nonequal** cross-section of tube guide 10 corresponding to a **nonequal** cross-section of the claimed

Art Unit: 3656

hole. It is further noted that for clarity, the rejection was explained to applicants' representative, Blake Tankersley, on 5/5/09.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

1. Claims 1-3, 7, 8, 9, 11-13, 15, 28, 29, 32, and 33, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over JP 4-116051 in view of Rohlinger US 5,373,755.

JP 4-116051 discloses:

- a screw shaft (1) including a spiral-shaped ball rolling groove (1a) formed in an outer peripheral surface thereof;
- a nut (2) including a spiral-shaped ball rolling groove formed in an inner peripheral surface thereof;
- a plurality of balls (3) disposed in a ball rolling passage formed by the two ball rolling grooves;
- a ball circulation tube (5) forming a ball circulation passage and including
 a ball scooping portion (5a) in an end portion thereof,
- a tube guide insertion hole (2c) is formed on the nut at a position where
 the ball scooping portion is inserted,

Art Unit: 3656

a tube guide made of resin (7, also see Japanese rejection) via which the
 ball circulation tube is mounted onto the nut.

- the tube guide (7) comprising: a top surface; a bottom surface; and a side surface connecting the top surface and the bottom surface (see figure 3, tube guide 7 has top and bottom surfaces and a cylindrical side surface),
- wherein a scooping portion insertion hole is formed so as to penetrate
 from the top surface to the bottom surface (see figure 3),
- the ball scooping portion is inserted into the scooping portion insertion hole (see figure 3),
- a tube guide insertion hole is formed on the nut at a position where the ball scooping is inserted (see figure 3).
- the side surface has a shape matched to an inner shape of a tube guide insertion hole (see figure 3),
- the scooping portion insertion hole has an inner shape matched to an outer shape of the ball scooping portion (see figure 3).
- wherein the side surface is formed in a cylindrical shape (see figures 1 and 3)
- wherein an axial line of the cylindrical shape is set perpendicular to an axial line of the nut (see figures 2 and 3)
- wherein the tube guide is made of elastic material (because all materials have a modulus of elasticity, the tube guide is made of an elastic material).

Art Unit: 3656

 wherein the tube guide is interposed between the ball scooping portion and the tube guide insertion hole without any clearance between the ball scooping portion and the tube guide insertion hole (see figure 3).

- Wherein the top surface is chamfered in a smooth arc manner (see figure
 3, top surface is curved matching shape of radius in tube)
- Wherein the top surface of the tube guide and the installation surface are disposed on a same plane on both sides of the tube guide (see top surfaces of 2b and 2c in same plane)

JP 4-116051 discloses a ballscrew with a recirculation tube guide. JP 4-116051 does not disclose an installation surface on which a lower surface of the ball circulation tube contacts. Rohlinger teaches an installation surface on which a lower surface of the ball circulation tube contacts (see figures 3 and 4). Because both JP 4-116051 and Rohlinger teach ballscrews with recirculation tube tube guides, it would have been obvious to one having ordinary skill in the art at the time of the invention to provide an installation surface on which a lower surface of the ball circulation tube contacts to achieve the predictable result of recirculating balls within a ballscrew.

2. Claims 1-3, 7- 9, 11-13, 15, 30 and 31, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over Conant 2,882,742 in view of Merkel US 3,379,643.

Conant discloses:

Art Unit: 3656

a screw shaft (10) including a spiral-shaped ball rolling groove (11) formed
 in an outer peripheral surface thereof;

- a nut (12) including a spiral-shaped ball rolling groove (13) formed in an inner peripheral surface thereof;
- a plurality of balls (16) disposed in a ball rolling passage formed by the two ball rolling grooves;
- a ball circulation tube (17) forming a ball circulation passage and including a ball scooping portion in an end portion thereof,
- a tube guide insertion hole is formed on the nut at a position where the ball scooping portion is inserted (see figure 6),
- a tube guide (35) via which the ball circulation tube is mounted onto the nut.
- the tube guide (35) comprising: a top surface; a bottom surface; and a side surface connecting the top surface and the bottom surface (see figure 6),
- wherein a scooping portion insertion hole is formed so as to penetrate
 from the top surface to the bottom surface (see figure 6),
- the ball scooping portion is inserted into the scooping portion insertion hole (see figure 6),
- a tube guide insertion hole is formed on the nut at a position where the ball scooping is inserted.

 the side surface has a shape matched to an inner shape of a tube guide insertion hole (see figure 6),

Page 8

- the scooping portion insertion hole has an inner shape matched to an outer shape of the ball scooping portion (see figure 6).
- wherein the side surface is formed in a cylindrical shape (see figure 6)
- wherein an axial line of the cylindrical shape is set perpendicular to an axial line of the nut (see figure 6)
- wherein the tube guide is made of elastic material (because all materials have a modulus of elasticity, the tube guide is made of an elastic material).
- wherein the tube guide is interposed between the ball scooping portion
 and the tube guide insertion hole without any clearance between the ball
 scooping portion and the tube guide insertion hole (see figure 6).

Conant does not disclose resin.

Merkel teaches resin (C1/L24-35) for the purpose of increasing flexibility and magnetic strength while reducing the expense of rigid metallic magnets (C1/L24-35).

It would have been obvious to one having ordinary skill in the art at the time of the invention to modify the teachings of Conant and provide a magnetic resin, as taught by Merkel, for the purpose of increasing flexibility and magnetic strength while reducing the expense of rigid metallic magnets.

Art Unit: 3656

3. Claims 4-6, 10 and 14, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over JP 4-116051 in view of Rohlinger US 5,373,755 and further in view of Ebina et al. US 6,089,117.

JP 4-116051 in view of Rohlinger discloses all of the claimed subject matter as described above. JP 4-116051 in view of Rohlinger does not disclose wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of the ball screw.

Ebina et al. teach wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of a ball screw (see figure 8) for the purpose of achieving smooth circulation of balls (C16/L45-60).

It would have been obvious to one having ordinary skill in the art at the time of the invention to modify the teachings of JP 4-116051 in view of Rohlinger and provide wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of a ball screw, as taught by Ebina et al., for the purpose of achieving smooth circulation of balls.

JP 4-116051 further discloses:

- wherein the tube guide is made of elastic material (because all materials have a modulus of elasticity, the tube guide is made of an elastic material).
- 4. Claims 4-6, 10 and 14, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over Conant 2,882,742 in view of Merkel US 3,379,643, and

further in view of Rohlinger US 5,373,755, and further in view of Ebina et al. US 6,089,117.

Conant discloses all of the claimed subject matter as described above. Conant does not disclose wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of the ball screw.

Ebina et al. teach wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of a ball screw (see figure 8) for the purpose of achieving smooth circulation of balls (C16/L45-60).

It would have been obvious to one having ordinary skill in the art at the time of the invention to modify the teachings of Conant and provide wherein the scooping portion insertion hole has a ball circulation passage scooping angle set so as to correspond to the a lead angle of a ball screw, as taught by Ebina et al., for the purpose of achieving smooth circulation of balls.

Conant further discloses:

- wherein the tube guide is made of elastic material (because all materials have a modulus of elasticity, the tube guide is made of an elastic material).
- 5. Claims 28 and 29, as best understood, are rejected under 35 U.S.C. 103(a) as being unpatentable over Conant 2,882,742 in view of Merkel US 3,379,643, and further in view of Rohlinger US 5,373,755.

Conant discloses all of the claimed subject matter as described above. Conant does not disclose a chamfered top surface.

Rohlinger teaches a chamfered top surface (see figures 4 and 6 @ 41) for the purpose of closely supporting a circulation tube while allowing for a radius to smoothly guide balls (C6/L55-65), thus avoiding an abrupt change in ball direction and improving operational efficiency.

It would have been obvious to one having ordinary skill in the art at the time of the invention to modify the teachings of Conant and provide a chamfered top surface, as taught by Rohlinger, for the purpose of closely supporting a circulation tube while allowing for a radius to smoothly guide balls, thus avoiding an abrupt change in ball direction and improving operational efficiency.

Response to Arguments

6. Applicant argues "However, neither JP '051 or Conant disclose or suggest this recitation. Specifically, JP '051 and Conant both have a step like portion towards the bottom of the hole and do not have a through hole which has a uniform cross section all the way through the entire depth of the hole. Also, neither Rohlinger, Merkel, or Ebina cure this deficiency. Specifically, none of the cited references show a hole which has a uniform cross section all the way through the entire depth of the hole. Also, none of the cited references disclose any advantages to being able to use an ordinary machining tool in order to be able to machine the tube guide insertion hole".

In response, it is submitted that the limitation being argued is indefinite as discussed above. Specifically, it appears as if applicants own invention does not have

Art Unit: 3656

the instant feature being claimed. The examiner asserts, that the amended claims has misconstrued the structure of the instant invention based upon applicants' figures 1 and 3. However, as can be seen in applicants' figure 4, the shape of tube guide 10 corresponds to the shape of tube guide insertion hole 9. It can also be seen that from this angle, that is to say, an axial view, the tube guide insertion hole would have a **unequal** cross section as outlined by applicants' figure 4d.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to TERENCE BOES whose telephone number is (571)272-4898. The examiner can normally be reached on Monday - Friday 9:00 AM - 4:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Richard Ridley can be reached on (571) 272-6917. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 3656

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Terence Boes/ Examiner, Art Unit 3656

/William C. Joyce/ Primary Examiner, Art Unit 3656